

Ozone: Simplified

Specifications & Requirements

**Enclosure**

Sealed NEMA 12 with Integral Cooler *Optional: NEMA 4X with Integral Cooler*
 Minimum Clearance: Front/Back/Right 36 in (915 mm) / Left 18 in (457.5 mm)
 Dimensions (LxDxH): 42" (1,062 mm) x 37" (933 mm) x 83" (2,107 mm)
 Weight: 1,200 lbs (545 kg)

Facility Connection Requirements

Oxygen Inlet: 3/4" Tube
 Ozone Outlet: 3/4" Tube
 Cooling Water Supply (CWS) & Return (CWR): 3/4" Tube
 Electrical Service: 230 VAC/3ph/50-60Hz/ 60A (39 FLA)
 Compressed Air Feed: 1/4" Push Lock Fitting

Ozone Output

Ozone Output (LOX): Up to 45.6 kg/d (100.5 ppd) @ 10% concentration / Up to 51.6 kg/d (113.8 ppd) @ 8% concentration
Ozone Output (PSA): Up to 38.4 kg/d (84.7 ppd) @ 10% concentration Up to 42.0 kg/d (92.6 ppd) @ 8% concentration
 Outlet Pressure: 20 psig *Optional: up to 25 psig*

Oxygen Requirements

PSA, VSA, VPSA or LOX O₂ Acceptable
 Oxygen Requirement at 10% concentration: 116.5 slpm per kgO₃ (52.9 slpm per lbO₃)
 Liquid Oxygen (LOX) Feed: Dew Point: <-80C (-112F)
 PSA/VSA Oxygen Feed: oxygen concentration ≥ 93%
 Max 0.1 µm Filter Inlet (*Upon request*)
 N₂ Feed NOT required.

Cooling Water Requirements

Type: Closed-Loop Chilled Water
 Fluid: Food Grade Glycol-Water Blend (*30/70 blend, not included*)
 Typical Required Cooling Water Flow: ~12 gpm
 Cooling Load: ~4.25 Ton

Controls & Communication

Schneider Electric Modicon M251 PLC Controller
 15" RedLion[™] Color Touch Screen HMI
 Remote Access: Ethernet/IP/Webserver Interface. Ethernet Switch Provided.
Optional: Cellular Modem (Cell Service Not Included)
 Uninterruptible Power Supply

Controls Routines

All Routines Available at Fixed or Variable O₃ % BW
 Automatic: PID ORP (mv) or PID DO₃ (ppm)
 Manual: Fixed Output (ppd or kg/h) or Full Manual

Accessories & Instrumentation

- 15 kVA Step Down Transformer
- Enclosure Ambient O₃ Analyzer
- Enclosure Ambient Temperature Transmitter
- O₂ Inlet Mass Flowmeter & Manual Rotameter
- O₂ Inlet Temperature Transmitter
- O₂ Inlet Pressure Transmitter
- O₃ Outlet Pressure Transmitter
- O₃ High Concentration Analyzer
- Inlet/Outlet Cooling Water Temperature

Compliance & Certifications

- UL 508A Listed, CSA, CE

Ozone: Simplified

Footprint Overview

