

Ozone: Simplified

Specifications & Requirements

**Enclosure**

Sealed NEMA 12 with Integral Cooler **Optional: NEMA 4X**

Minimum Clearance: Front/Back/Right 36 in (915 mm) / Left 18 in (457.5 mm)

Dimensions (LxDxH): 43" (1,075 mm) x 37" (925 mm) x 95" (2,275 mm)

Weight: 1,700 lbs (771 kg)

Facility Connection Requirements

Oxygen Inlet: 3/4" Tube

Ozone Outlet: 3/4" Tube

Cooling Water Supply (CWS) & Return (CWR): 3/4" Tube

Electrical Service: 208VAC/3ph/50-60Hz/ 110A (79 FLA) – (480/600/400 VAC -> 208VAC Stepdown Transformer provided by Pinnacle – See below).

Compressed Air Feed: 1/4" Push Lock (~1 cfm)

Ozone Output

Ozone Output (LOX): Up to 91.2 kg/d (201.1 ppd) @ 10% concentration, 103.2 kg/d (227.5 ppd) @ 8% concentration.

Ozone Output (PSA): Up to 76.8 kg/d (169.3 ppd) @ 10% concentration, 84 kg/d (185.2 ppd) @ 8% concentration.

Outlet Pressure: Up to 25 psig

Oxygen Requirements

PSA, VSA, VPSA or LOX O₂ Acceptable

O₂ Requirement: 116.55 slpm/Kg-O₃ (52.87 slpm/lb-O₃) at 10% operating concentration.

PSA/VSA Oxygen Feed: oxygen concentration ≥ 93%

Max 0.1 µm Filter Inlet (Upon request)

N₂ Feed NOT required.

Cooling Water Requirements

Type: Closed-Loop Chilled Water

Fluid: Food Grade Glycol-Water Blend (30/70 blend, not included)

Typical Required Cooling Water Flow: ~20 gpm

Cooling Load: ~8.5

Controls & Communication

PLC: Allen Bradley CompactLogix **Optional: Schneider and Siemens.**

HMI: Allen Bradley PanelView Color 15" **Optional: Schneider and Siemens.**

Remote Access: Ethernet/IP/Webserver Interface. Ethernet Switch Provided.

Uninterruptible Power Supply

Controls Routines

Routines: Fixed or Variable O₃ %BW

Automatic: PID ORP (mv) or PID DO₃ (ppm)

Manual: Fixed Output (ppd or kg/h) or Full Manual

Accessories & Instrumentation

- 45 kVA Step Down Transformer
- Enclosure Ambient O₃ Analyzer
- Enclosure Ambient Temperature Transmitter
- O₂ Inlet Mass Flowmeter & Manual Rotameter
- O₂ Inlet Temperature Transmitter
- O₂ Inlet Pressure Transmitter
- O₃ Outlet Pressure Transmitter
- O₃ High Concentration Analyzer
- Inlet/Outlet Cooling Water Temperature

Compliance & Certifications

- UL 508A Listed, CSA, CE

Ozone: Simplified

Footprint Overview

